



## Switch Mode Power Supply

Supplier: J. Schneider Elektrotechnik GmbH  
 Type : **UNOTEC 2420 N**  
 Art.-No. : NFPG 1311G03001



### Short description

The **UNOTEC 2420N** is a switch mode power supply of the latest generation, which is characterized by its high efficiency and minimum power loss. It features Power Boost and Hyper Boost function. The **UNOTEC N** can be operated redundantly. Operation in series (2 units max.) and parallel operation (up to 5 devices) are possible. Because of modern architecture, it can work in temperatures up to 60 ° C without load reduction.

### Input

Nominal voltage	100-240 VAC 100-230 VDC
Voltage range	85-265 VAC 90-250 VDC
Power distribution systeme	TN-S, TN-C, TT, IT mains
Nominal frequency	50 / 60 Hz ±6 %
Nominal current	5,3 A @ 100 V AC/DC 4,8 A @ 110 V AC/DC 2,3 A @ 230 V AC/DC
Inrush current	I <sub>eff</sub> / I <sub>RMS</sub> : 3,5 A I <sub>t</sub> : 2 A <sup>2</sup> s
Efficiency	94,1 % 94,0 % @ 24 VDC/15 A Load 91,7 % @ Input 110 VAC; 24 VDC/20 A Load
Power losses	29,9 W 22,8 W @ 24 VDC/15 A Load 43,3 W @ Input 110 VAC; 24 VDC/20 A Load
Power factor	0,96 0,95 @ 24 VDC/15 A load 0,99 @ input 110 VAC; 24 VDC/20 A load
No-load power lossos	≤ 3 W @ 24 VDC/0 A load
Start-up time	< 400 ms @ input 100-230 VAC
Recommended external fuse max	20 A (T) in building installation
Recommended circuit breaker	B6
Internal device protection	10 A (T)

### Output

Voltage	24 VDC
Voltage adjustable	24-28 VDC / potentiometer in front plate
Factory setting	24,1 VDC ±0,2 V
Residual Ripple	< 50 mV eff / rms
Spikes	< 200 mV ss / p-p
Nominal current	24 VDC / 20 A (up to 60 °C) 28 VDC / 17 A (up to 60 °C)

03001D02-130808

Technical modifications possible!



Input failure bridging	≥ 30 ms @ input 100 VAC; 24 VDC/20 A load
Hold-up time	30 ms
“Power boost“ current	IN x 150% for min. 4 s without voltage variation
“Hyper boost“ current	IN x 200% for min. 20 ms @ 60°C
Short circuit current	After “power boost“ follows constant current: 20 A
Parallel connection	Max. 5 units
Serial operation	Up to 2 units in series to keep SELV at the output. If more than 2 units in series the output voltage exceeds the permissible voltage limit for SELV.

Output overload and short-circuit protected. With overload the output voltage begins to reduce. With over temperature the power supply unit turns off.

## Connection Input/Output

Type of connection	Spring clamp, push-in
Cable diameter stable	1,0–10 mm <sup>2</sup> / AWG 17–8
Cable diameter flexible	1,0–6 mm <sup>2</sup> / AWG 17–10
flexible with ferrule, with plastic sleeve	1,0–4 mm <sup>2</sup> / AWG 17–12
flexibel with ferrule, without plastic sleeve	1,0–6 mm <sup>2</sup> / AWG 17–10

## Connection Alarm

Type of connection	Spring clamp, push-in
Cable diameter stable	0,25–4 mm <sup>2</sup> / AWG 24–12
Cable diameter flexible	0,25–2,5 mm <sup>2</sup> / AWG 24–14
flexible with ferrule, with plastic sleeve	0,25–1.5 mm <sup>2</sup> / AWG 24–16
flexibel with ferrule, without plastic sleeve	0,25–2.5 mm <sup>2</sup> / AWG 24–14

Classification of climatic environmental conditions	Class 3K3 according to EN 60721
Relative humidity	5 ... 95%, No condensation
Environmental temperature	-25 ... +60 °C
Storage temperature	-40 ... +85 °C
MTBF und / and MTTF nach / according to DIN EN 61709:1999-01, SN 29500, DIN EN ISO 13849-1:2008-12	

## Insulation voltages

Input-output	Type test: 3000 VAC; Factory test: 2500 VAC 1s
Input-PE	Type test: 1700 VAC; Factory test: 2500 VAC 1
Output-PE	Type test: 500 VAC; Factory test: 400 VAC 1s

## Approvals



CE-marking in compliance with EMC directive 2004/108/EC and low-voltage directive 2006/95/EC and Directive 2011/65/EU (RoHS Directive) of THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (recast).

03001D02-130808

Technical modifications possible!



## Housing

Dimensions	125 x 85 x 138 mm (H x W x D)
Weight	1,26 kg
Protection class	I
Protection class of the housing	IP 20
Pollution degree	2
Fixation	DIN-rail mounting TH 35 to EN 60715. Please consider the maximum permissible load of your mounting rail according to EN 60715.
Fitting position	Vertical
Material	Metal

## Standards:

EN 61204-3	
EN 55011 class B, group 1	EMI: class B; EMS: industrial environment class A
EN 61000-3-2	
EN 61000-3-3	
EN 61000-4-2 ESD	contact $\pm 6$ kV, air $\pm 8$ kV
EN 61000-4-3 HF-field	10 V/m
EN 61000-4-4 Burst	$\pm 2$ kV, 5/50 ns
EN 61000-4-5 Surge	AC mains input L1 $\rightarrow$ N (DM) $\pm 1$ kV/ $\pm 2$ kV/ $\pm 4$ kV DC output (+) $\rightarrow$ (-) (DM) / (+) v (-) $\rightarrow$ PE (CM) $\pm 0,5$ kV / $\pm 0,5$ kV
EN 61000-4-6 HF-asymm	10 V
EN 61000-4-11	
IEC 60068-2-6 Test Fc: Vibration	Vibration sinusoidal 5 - 17.8 Hz: 1.0 mm; 17.8 – 500 Hz: 2 g 10 cycles
IEC 60068-2-27 Test Ea: Shock	Shock, 15 g sinusoidal, Shock duration 11 ms
IEC / EN 60950-1	SELV
EN 60204-1	60 V / 1 sec
SEMI F47 – 0706	proof ( $\geq 160$ VAC)
EN 60950-1 Overvoltage category:	II
Operation up to	2000 m above NN

## Reliability

SN 29500  
IEC 61709