

FnIO G – Series :

GT-225F

GT-225F(16 Channels, Sink Output Terminal, 24Vdc/0.3A)

Specification Preliminary

Table of Contents

Table of Contents..... 2

History.....3

1.ENVIRONMENTSPECIFICATION..... 4

2.GT-225F(16 Channels Source Output Terminal)..... 5

 2.1.GT-225F Specification 5

 2.2.GT-225F Wiring Diagram..... 6

 2.3.GT-225F LED Indicator..... 7

 2.3.1.LED Indicator.....7

 2.3.2.Channel Status LED..... 7

 2.4.Mapping data into the image table.....8

 2.5.Parameter Data..... 9

History

REV.	PAGES	REMARKS	DATE	Editor
1.00	9		16.10.2017	Kim Hong Seok

Specification Preliminary

1. ENVIRONMENT SPECIFICATION


Environment specification	
Operation Temperature	-40°C to 70°C
Non-Operating Temperature	-40°C to 85°C
Relative Humidity	5% to 95% Non-condensing
Operating Altitude	2,000m
Mounting	
General specification	General specification
Shock Operating	IEC 60068-2-27
Vibration Resistance	Based on IEC 60068-2-6 Sine Vibration <ul style="list-style-type: none"> - 5 ~ 25Hz : ±1.6mm - 25 ~ 300Hz : 4g - Sweep Rate : 1 Oct/min, 20 cycles Random Vibration <ul style="list-style-type: none"> - 10 ~ 40 Hz : 0.0125 g²/Hz - 40 ~ 100 Hz : 0.0125 → 0.002 g²/Hz - 100 ~ 500 Hz : 0.002 g²/Hz - 500 ~ 2000 Hz : 0.002 → 1.3 x 10⁻⁴g²/Hz - Test time : 1hrs for each test
Industrial Emissions	EN 61000-6-4 : 2007 +A1:2011
Industrial Immunity	EN 61000-6-2 : 2005
Installation Position	Vertical and horizontal installation is available.
Product Certifications	CE, UL

2. GT-225F (16 Channels Sink Output Terminal)

2.1. GT-225F Specification

Items	Specification
Input Specification	
Output per module	16 Points Sink type
Indicators	16 Green output state
Output Voltage Range	Nominal 24Vdc, Min. 15Vdc ~ Max. 32Vdc
ON-state voltage drop	Max. 0.3Vdc @ 25°C / 0.5Vdc@ 70°C
ON-State Min. Current	1mA per channel
OFF-State Leakage current	Max. 20uA
Output Signal Delay	OFF to ON : 0.3mS maximum ON to OFF : 0.5mS maximum
Output Current Rating	Max. 0.3A per channel / Max. 4.8A per unit
Protection (VNS3NV04D-E)	Over Current limit: Min. 3.5A@ 25°C per each channels (VNS3NV04D-E) Thermal Shutdown : Min 3A@ 25°C per each channels (VNS3NV04D-E, Min 150°C) Short circuit protection
COMMON Type	16 points / 2COM (Single Common)
General specification	
Power dissipation	50mA maximum @ 5.0Vdc
Isolation	I/O to Logic : Photocoupler isolation
Field Power	Supply voltage : 24Vdc nominal Voltage range : 15~32Vdc Power dissipation: 30mA maximum @ 32.0Vdc
Wiring	I/O Cable Max. 0.32mm ² (AWG 22)
Weight	52g
Module Size	12mm x 99mm x 70mm
Environment Condition	Refer to '1. Environment Specification'


2.2. GT-225F Wiring Diagram



Pin No.	Signal Description	Signal Description	Pin No.
0	Output Channel 0	Output Channel 1	1
2	Output Channel 2	Output Channel 3	3
4	Output Channel 4	Output Channel 5	5
6	Output Channel 6	Output Channel 7	7
8	Output Channel 8	Output Channel 9	9
10	Output Channel 10	Output Channel 11	11
12	Output Channel 12	Output Channel 13	13
14	Output Channel 14	Output Channel 15	15
16	Common (Field Power 24V)	Common (Field Power 24V)	17

2.3. GT-225F LED Indicator

2.3.1. LED Indicator



LED No.	LED Function / Description	LED Color
0	OUTPUT Channel 0	Green
1	OUTPUT Channel 1	Green
2	OUTPUT Channel 2	Green
3	OUTPUT Channel 3	Green
4	OUTPUT Channel 4	Green
5	OUTPUT Channel 5	Green
6	OUTPUT Channel 6	Green
7	OUTPUT Channel 7	Green
8	OUTPUT Channel 8	Green
9	OUTPUT Channel 9	Green
10	OUTPUT Channel 10	Green
11	OUTPUT Channel 11	Green
12	OUTPUT Channel 12	Green
13	OUTPUT Channel 13	Green
14	OUTPUT Channel 14	Green
15	OUTPUT Channel 15	Green


2.3.2. Channel Status LED

Status	LED	To indicate
Not Signal	Off	Normal Operation
On Signal	Green	Normal Operation

2.4. Mapping data into the image table

- **Output Image Value**

Bit No	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
Byte0	D7	D6	D5	D4	D3	D2	D1	D0
Byte1	D15	D14	D13	D12	D11	D10	D9	D8



- **Output Module Data**

D7	D6	D5	D4	D3	D2	D1	D0
D15	D14	D13	D12	D11	D10	D9	D8

Specification Preliminary

2.5. Parameter Data

- Valid Parameter length: 4 Bytes
- Parameter Data

Bit No	Bit7	Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
Byte0	Fault Action (ch0~ch7)				0: Fault value, 1:Hold last state			
Byte1	Fault Action (ch8~ch15)				0: Fault value, 1:Hold last state			
Byte2	Fault value (ch0~ch7)				0:Off, 1:On			
Byte3	Fault value (ch8~ch15)				0:Off, 1:On			