



# Kontaktbuchse 1,5 mm geschlitzt

Einsatzbereich: - 623 Isolierkörper, 19-polig

TE Teile Nr.: 60-0070-011-000

IC Ref. Nr.: 60.070.11

## Elektrische Werte

Bemessungsstrom max. 10 A\*  
Durchgangswiderstand < 5 mOhm

## Werkstoff

Kontakt Messing, vergoldet

## Anschluss

Anschlussart/-bereich Crimp/ 0,14 - 1,0 mm<sup>2</sup>  
- für Isolationscrimp max.  $\varnothing 2,1$  mm  
Abisolierlänge 6 mm  
Crimpeinstellungen sind individuell zu wählen

## Mechanische Werte



Steckzyklen 500

## Werkzeuge (nicht im Lieferumfang enthalten)

digitale Crimpzange TE Teile Nr.: C0-0236-000-000  
IC Ref. Nr.: C0.236.00

(analoge Crimpzange TE Teile Nr.: C0-0201-000-000  
IC Ref. Nr.: C0.201.00

Positioniereinsatz für 1,5 mm Kontakte TE Teile Nr.: C0-0048-000-000  
IC Ref. Nr.: C0.048.00



## Hauptabmessungen

Kontaktbuchse





# Contact Socket 1.5 mm slotted

for: - 623 Insulation Insert, 19-pin

TE part number: 60-0070-011-000  
IC reference number: 60.070.11

## Electrical Data

rated current max. 10 A\*  
contact resistance < 5 mOhm

## Material

contact brass, gold plated

## Termination

cross-section crimp/ 0.14 - 1.0 mm<sup>2</sup>  
- for insulation crimp max.  $\varnothing$ 2.1 mm  
stripping length 6 mm  
crimp settings select individually

## Mechanical Data



Mating cycles 500

## Tools (not part of product contents)

digital crimping tool TE part no.: C0-0236-000-000  
IC ref. no.: C0.236.00

(analog crimping tool TE part no.: C0-0201-000-000  
IC ref. no.: C0.201.00

positioner for 1.5 mm contacts TE part no.: C0-0048-000-000  
IC ref. no.: C0.048.00)



**Main Dimensions**  
contact socket

Y6-C017-000-0EN issued: 20.04.2010/Ra; modified: 17.10.2018/KC

© 2018 TE Connectivity

TE Connectivity, TE connectivity (logo), intercontec (logo) and speedtec are trademarks.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this presentation, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this article are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

TE Connectivity Industrial GmbH  
Bernrieder Straße 15  
94559 Niederwinkling, Germany  
+49 9962 2002 - 0  
[intercontec@te.com](mailto:intercontec@te.com)  
[www.intercontec.biz](http://www.intercontec.biz)



\* for max. wire cross-section